

FlexFix® Product Code DUP 9 Material Stainless Steel

The longlive snap fastening system for maritime and other technical applications





The longlive snap fastening system for maritime and other technical applications

Boats, yachts and accessories are exposed to enormous weather influences, such as dirt and salt water. Weatherproof boat covers are usually fitted with standard snap fasteners, which are subject not only to corrosion but also to lateral forces caused by wind and waves. Over time, the fastener can become stiff or even unusable and may pose a safety risk.

The new FlexFix® in Stainless Steel from YKK STOCKO FASTENERS offers a solution to these issues, offering enhanced durability and resistance to corrosion. The special design of the socket with the proven technology used in the FlexFix® range replaces the metal spring part with a spring-elastic plastic. This innovative design can absorb lateral forces (shear force) particularly well, allowing for more tension on the entire snap fastening system without tilting.

Additionally, the new eyelet is compatible with identical systems, offering a convenient optimization for already installed stud components.

Besides the stud and post combination, a stud with an integrated stainless-steel screw is also available.

SYSTEM CONSTRUCTION



Alternatively with integrated stainless-steel screw

SIZE

The socket is shown in its original size (ø 14.3 mm).









Colour example, inlay currently only available in the colour 'nature'.

APPLICATION AREAS

- Boats, motorhomes, etc.
- Persennings
- Curtains and tarpaulins
- Life jackets
- Interior fittings

BENEFITS

- Corrosion-resistant due to stainless steel
- Resistant to salt water
- High absorption of shear forces
- Robust opening and closing behaviour
- High pressure resistance
- High long-term resistance wear-resistant
- Thermostable
- Compatible with SNAD® and others
- Plastic inlay of the socket on request in different colours

FlexFix® Product Code DUP 9 in Stainless Steel					
	Product	Material	Ø [mm]	Height [mm]	Info
CAP					
-	DK 606/6.040S CAP U (JG4-0000-LE7C)	Stainless steel	15,5	8,9	
SOCKET					
	DPO 9	Stainless steel, Plastic	14,3	4,2	
STUD					
9	DRK 9.040S STUD U (AH7-0000-303C)	Stainless steel	14	4,45	
-	AJ7-0-303 SCREW STUD	Stainless steel	12,7	16,3	Stud with integrated stainless-steel screw
POST					
J	DRN 9.040S POST U (AJ1-0000-303C)	Stainless steel	14,2	7,9	

Copyright © 2024 YKK STOCKO FASTENERS GmbH Wuppertal / Germany

All rights reserved. Reprints, reproductions and translations of

YKK STOCKO FASTENERS GmbH advertising materials are covered by the copyright of YKK STOCKO FASTENERS GmbH and are only permitted with the prior written consent of YKK STOCKO FASTENERS GmbH.

Article photos and drawings of the closure and fastening systems shown may deviate from the original size or original geometry of the products and color. The dimensions given are non-binding guide values.

YKK STOCKO FASTENERS GmbH Kirchhofstrasse 52 · 42327 Wuppertal Germany T +49 202 - 7493 - 0 F +49 202 - 7493 - 446 info_stocko.deu@ykk.com www.stocko-ykk.de

